


1、 Mechanical Outline(Unspecified Tolerances is: $\pm 0.3\text{mm}$) Color: Pure Green



2、 Lamp: 1 x 1 = 1

3、 Storage & Soldering Conditions:

- 1 Store with care. Storing the units in bad condition will cause the reflector sheet and decrease it's adhesive power. Storage the products under the condition: temperature ($25^{\circ}\text{C} \pm 10^{\circ}\text{C}$) and humidity ($65^{\circ}\text{CRH} \pm 20^{\circ}\text{CRH}$) our recommendation.
- 1 The soldering Temperature is $260 \pm 5^{\circ}\text{C}$ and Soldering Time should be less than 3 sec, and soldering iron power should be less than 30W.
- 1 The soldering point should be farther than 1.6mm from body.

4、 ABSOLUTE MAXIMUM RATINGS (Single Lamp)
(Unless specified, The Ambient temperature $T_a = 25^{\circ}\text{C}$)

Item	Symbol	Condition	Rating	Unit
Absolute maximum forward current	Ifm		30	mA
Peak forward current	Ifp	1 msec Plus 10% Duty Cycle	50	mA
Reverse Voltage	Vr		5	V
Power dissipation	Pd		100	mW
Operating Temperature Range	Topr		-20~+70	$^{\circ}\text{C}$
Storage Temperature Range	Tstg		-20~+75	$^{\circ}\text{C}$

5、ELECTRICAL-OPTICAL CHARACTERISTICS (Single Lamp)
 (Unless specified, The Ambient temperature Ta=25°C)


Item	Symbol	Min.	Typ.	Max.	Unit	Condition
Forward Current	If	15	20	25	mA	Vf=3.3V
Forward Voltage	Vf	3.0	3.3	3.6	V	If=20mA
Reverse Current	Ir			10	μA	Vr=5V
Luminance	Lv		50		cd/m ²	Vf=3.3V
Wave Length	λp	520	525	530	nm	Vf=3.3V

6、STATIC ELECTRICITY AND SURGE

- 1 Static electricity and surge will damage the LEDs. It is recommended to use a wrist band or anti-electrostatic glove when handling the LEDs.
- 1 All devices, equipment and machinery must be properly grounded.

7、LED Electrical Characteristics

Forward Current VS. Ambient Temperature



Relative Intensity VS. Ambient Temperature

