


PIN#	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22
COM	1G	1F	1A	1B	2G	2F	2A	2B	3G	3F	3A	3B	4G	4F	4A	4B	5G	5F	5A	5B	6G	6F
PIN#	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40	41	42	43	44
COM	6A	6B	7G	7F	7A	7B	8G	8F	8A	8B	COM	COM	1E	1D	1C	1H	2E	2D	2C	2H	3E	3D
PIN#	45	46	47	48	49	50	51	52	53	54	55	56	57	58	59	60	61	62	63	64	65	66
COM	3C	3H	4E	4D	4C	4H	5E	5D	5C	5H	6E	6D	6C	6H	7E	7D	7C	7H	8E	8D	8C	8B



DISPLAY MODE	TV/POSITIVE/TRANSPARENT	DUTY STATIC	BUS	4		MODEL NO	FP-1209P	DWN:	NOV2007/217	UNIT	mm
VIEWING ANGLE	6:00 O'CLOCK	SAMPLE	<input type="checkbox"/> $\frac{1}{6}$ <input type="checkbox"/> $\frac{1}{10}$	3		CUSTOMER NO		CHK:		SCALE	1 : 1
DRIVING VOLTAGE	5.0V	APPLICATION:	<input type="checkbox"/> INSTRUMENT <input type="checkbox"/> HOME APPLIANCESS <input type="checkbox"/> AIR-CONDITION <input type="checkbox"/> TELEPHONE <input type="checkbox"/> AUTOMOBILE <input type="checkbox"/> OTHER	2		CUSTOMER		APP:		SHEET	SHEET 1 OF 1
OPERATING TEMP	-20° C TO 80° C			1							
STORAGE TEMP	-40° C TO 100° C										
CONNECTOR	PIN W537110C										
						CROSSING POINTS IN THE VIEW: YES <input type="checkbox"/> NO <input type="checkbox"/>	TOLERANCES UNLESS OTHERWISE STATED	X: ±0.10	XX: ±0.20	ANGLE: ±0.1°	