



PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20
COM	COM	1G	1E	1D	1C	2E	2D	2C	3E	3D	3C	DP3	4E	4D	4C	DP4	5E	5D	5C	5B
PIN	21	22	23	24	25	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40
COM	5A	5F	5G	4B	4A	4F	4G	3B	3A	3F	3G	COL2	2B	2A	2F	2G	COL1	1B	1A	1F

DISPLAY MODE	TN/POSITIVE/REFLECTIVE	DUTY	STATIC	BINS	4																
VIEWING ANGLE	6:00 0'CLOCK	SAMPLE	1/8	1/16	3																
DRIVING VOLTAGE	3.0V	APPLICATION:	<input type="checkbox"/> INSTRUMENT <input type="checkbox"/> HOME APPLIANCE <input type="checkbox"/> AIR-CONDITION <input type="checkbox"/> TELEPHONE <input type="checkbox"/> AUTOMOBILE <input type="checkbox"/> OTHER																		
OPERATING TEMP	-10° C TO 55° C	1	2	3	4																
STORAGE TEMP	-20° C TO 65° C	WER	MODIFY CONTENTS	DATE																	
CONNECTOR	PIN	CROSSING POINTS IN THE VIEW: YES <input type="checkbox"/> NO <input checked="" type="checkbox"/>			TOLERANCES	UNLESS OTHERWISE STATED X: ±0.10 XX: ±0.20 ANGLE ±0.1°															
Longtech Optics Co., Ltd.																					
MODEL NO	FP-1138P	DWN:	NOV 2006128	UNIT	mm																
CUSTOMER NO		CHK:		SCALE	1 : 1																
CUSTOMER		APP:		SHEET	SHEET 1 OF 1																