


PIN	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25
COM	COM	/	/	/	1E	1D	1C	DP1	2E	2D	2C	DP2	3E	3D	3C	DP3	4E	4D	4C	4B	4A	4F	4G	3B	3A
PIN	26	27	28	29	30	31	32	33	34	35	36	37	38	39	40										
COM	3F	3G	COL	2B	2A	2F	2G	/	1B	1A	1F	1G	/	/	/										



DISPLAY MODE	TM/POSITIVE/REFLECTIVE	DUTY (STATIC) BIAS		4			MODEL NO	FP-1203PA	DWN:	NOV 20080418	UNIT	mm
VIEWING ANGLE	6:00 0' CLOCK	SAMPLE	<input type="checkbox"/> <input type="checkbox"/>	3			CUSTOMER NO		CHK:		SCALE	1 : 1
DRIVING VOLTAGE	5.0V	APPLICATION:	<input type="checkbox"/> INSTRUMENT <input type="checkbox"/> HOME APPLIANCE <input type="checkbox"/> AIR-CONDITION <input type="checkbox"/> TELEPHONE <input type="checkbox"/> AUTOMOBILE <input type="checkbox"/> OTHER	2			DATE		APP:		SHEET	SHEET 1 OF 2
OPERATING TEMP	-30° C TO 80° C	WER	1	MODIFY CONTENTS			CUSTOMER				SHEET	SHEET 1 OF 2
STORAGE TEMP	-40° C TO 85° C	CROSSING POINTS IN THE VIEW:	YES <input type="checkbox"/> NO <input type="checkbox"/>	TOLEANCES	UNLESS OTHERWISE STATED	X:±0.10 XX:±0.20	ANGLE	±0.1°				
CONNECTOR	PIN											

Longtech Optics Co., Ltd.